SPECIFICATION SHEET

JFX600-2513

UV-LED FLATBED PRINTER

98.43” x 51.18”

Blazing Speed, High Definition

The Mimaki JFX600-2513 UV-LED flatbed printer is the fastest model in the world’s best-selling JFX Series line. Productivity has never looked better. This state-of-the-art printer is geared for high accuracy, high image quality, and blazing speed.

- 16 print heads
- Print speeds up to 2,152 square feet per hour
- Equivalent to 67 boards per hour
- On machine job and maintenance control via Mimaki Print Controller (MPC)
- Industry leading Mimaki Core Technologies
- Print area of 98.425” x 51.181”; up to 2.362” thick
- Production workflow ready with MDL support
- Eco-friendly with low VOC, GREENGUARD Gold certified UV-LED inks
- Compact design

For best results, always use Mimaki original inks.

Mimaki JFX600-2513

Printhead	Sixteen on-demand piezo heads in a staggered array
Print Resolutions	600 x 600dpi, 600 x 1,200dpi, 1,200 x 1,200dpi
Print Speed (4 Color Mode)	up to 2,152.78 SqFt/Hr (200.0 m2/h)
Maximum Print Area	98.43” x 51.18” (2,500 x 1,300 mm)
Maximum Media Width	98.43” (2500 mm)
Maximum Media Thickness	up to 2.36” (60 mm)
Maximum Media Weight	110.2 lbs. (50kg/m²)
Ink Type	U.S. & Canada- LH-100, LUS-120, LUS-150 Mexico, Central & South America- LH-100, LUS-120, LUS-150
Interface	Ethernet 10,000 BASE-T
Power Supply	AC 200 – 240 V, 50/60 Hz
Power Consumption	x3 AC200-240±10% ~16kVA 50/60Hz±1Hz
Operational Environment	Temperature 68° – 86° F (15-30° C) Humidity: 35–65 % RH (Non condensing)
Dimensions (W × D × H)	207.48” x 110.24” x 62.99” (5,300×2,850×1,700mm)
Weight	2, 645.5 lbs. (1,200 kg)
Certifications	UL 775 ETL, CE Marking (EMC Directive,Low Voltage Directive, Machinery Directive), RoHS / REACH / EAC

UV-LED FLATBED PRINTER

98.43” x 51.18”

ATLANTIC GRAPHIC SYSTEMS

410-290-8200
info@agspress.com
atlanticgraphicsystems.com

9687 Gerwig Lane Suite B, Columbia MD 21046

Please visit us at: www.mimakiusa.com

Mimaki USA, Inc.
150-A Satellite Blvd NE, Suwanee, GA 30024

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2020, Mimaki USA, Inc.

Rev. 04/20/22